

REQUEST FOR QUOTATION (GIKI/PD/RFQ-19/2024-25)

Sealed quotations, in Pak rupees on D.D.P basis, are invited from registered suppliers/authorized dealers/distributors and manufacturers for supply of the following items:

S#	Item Description	Annexures
1.	Lab & Workshop Supplies	Detail attached at Annexure- A & B
2.	Workshop Tools	Detail attached at Annexure- C

Interested parties are requested to keep following points into consideration before submitting their quotations.

- Your quotations must be delivered to the office of the undersigned on or before 4 October Friday 2024, at 3:00 PM. Any quotation received later than the scheduled date and time will be rejected and returned unopened.
- All quotations must be valid for a period of Thirty (30) days from the closing date of the Request for Quotation.
- The quotation shall be completed and signed by an authorized representative of the supplier.
- The quoted price should include all applicable Govt taxes.
- Delivery will be made to GIK Institute, Topi, Swabi.
- Payment will be made within 2-3 weeks after acceptance of the items subject to deduction of taxes as per law.
- In the case of any arithmetical discrepancy between the unit rate and the total amount quoted, then the unit rate shall prevail both for the evaluation of quotations and for the subsequent purchase order.

Assistant Director, Procurement Department, GIK Institute, Topi, Swabi (KP)

Ph: 0938-281026 Ext. 2444, Email: taufeeq@giki.edu.pk

ANNEXURE-A

S#	Item Description	Qty Req.	A/C Unit
1	Hydrogen per oxide (H2O2)	01	Liter
2	Epoxy Resin	05	Liter
3	Epoxy Hardner	05	Liter
4	Nickel (II) Sulphate Hexahydrate	01	Kg
5	Sodium Hypophosphite	01	Kg

ANNEXURE-B

S#	Item Description	Qty	A/C Unit
1	Molybdenum Wire, 500 meters (Dia: 0.182mm) Purity	02	Spool
	99.95%		_
2	Cutting Fluid for Wire EDM (JR3A Emulsifield)	10	Kg
3	Kerosene Oil	05	Liter

ANNEXURE-C

S#	Item Description	A/C Unit	Qty
1.	Concrete Rebar Locators, Concrete Wall Scanner, Rebar	Nos.	01
	Scanner:		
	Power Supply: 2 x 1.5 V AA Batteries		
	Voltage Range: 3.6V to 1.8V		
	Dimensions: 205 x 92 x 41mm (8 x 3.6 x 1.6")		
	Temperature Range: -10°C to 60°C (14°F to 140°F)		
	Humidity Range: 0 to 100% rH		
	Protection Range: IP54 (Picture attached at		
	Annexure-D)		
2	Strain Guage	Nos.	10
3	Epoxy for strain Guages	Nos.	05
4	Electrical Extension Boards	Nos.	02

ANNEXURE-D

